

Heavy Duty Black Belt Specifications

(CLASS B)



ITEM	DESCRIPTION	WEIGHT	U/M	THICKNESS	MIN. PULLEY	FLEXCO PLATE	FLEXCO HINGE	ALLIGATOR HINGE	CLIPPER	ALLIGATOR
B1501X0	2-PLY #150 1/32 X BARE	0.069	PIW	9/64"	6"	NA	NA	RS62	UX1	#15
B1501X1	2-PLY #150 1/32 X 1/32	0.088	PIW	5/32"	6"	NA	NA	RS125	U3-1	#15, #20
B1502X1	2-PLY #150 1/8 X 1/32	0.15	PIW	1/4"	10"	140	375, R2	RS187	NA	#27
B1502X16	2-PLY #150 1/8 X 1/16	0.157	PIW	9/32"	10"	140	375, R2	RS187*	NA	#27, #35
B2201X1	2-PLY #220 1/16 X 1/16	0.12	PIW	1/4"	10"	140, 1	375, R2	RS187	NA	#27
B2201X1SOR	2-PLY #220 1/16 X 1/16 SOR	0.12	PIW	1/4"	10"	140, 1	375, R2	RS187	NA	#27
B2203X1	2-PLY #220 3/16 X 1/16	0.19	PIW	3/8"	10"	140, 190	375, 550, R5	NA	NA	#45, #55
B2202X0MOR	2-PLY #220 1/8 X BARE MOR	0.143	PIW	3/16"	10"	140, 1	R2	RS187	U3-1	#20, #25
B2202X16	2-PLY #220 1/8 X 1/16	0.17	PIW	5/16"	10"	140, 1	375, R2, R5	NA	NA	#35
B2202X1CL	2-PLY #220 1/8 X 1/16 CLEAT TOP	0.21	PIW	1/2"	10"	140, 1	375, R2, R5	NA	NA	#35
B2203X1HA	2-PLY #220 3/16 X 1/16 HOT ASPHALT	0.181	PIW	3/8"	10"	140,190	375, 550, R5	NA	NA	NA
B2203X1HT	2-PLY #220 3/16 X 1/16 400 DEGREE	0.18	PIW	3/8"	12"	140,190	375, 550, R5	NA	NA	NA
B2252X0MOR	3-PLY #225 1/8 X BARE MOR	0.155	PIW	1/4"	14"	140, 1	375,550,R2,R5	NA	NA	NA
B3303X0MOR	3-PLY #330 3/16 X BARE MOR	0.18	PIW	3/8"	16"	140, 190	375,550,R2,R5	NA	NA	NA
B3301X1	3-PLY #330 1/16 X 1/16	0.15	PIW	9/32"	16"	140, 1	375,R2,R5	NA	NA	#27,#35
B3303X1	3-PLY #330 3/16 X 1/16	0.221	PIW	7/16"	16"	140,190	550,R5,R5-1/2	NA	NA	NA
B3302X1CL	3-PLY #330 1/8 X 1/16 CLEAT TOP	0.26	PIW	5/8"	16"	140,190	375,550,R5	NA	NA	NA
B3303X1HT	3-PLY #330 3/16 X 1/16 400 DEGREE	0.215	PIW	7/16"	18"	140,190	550,R5,R5-1/2	NA	NA	NA
B3304X1	3-PLY #330 1/4 X 1/16	0.23	PIW	1/2"	16"	190	550,R5-1/2, R6	NA	NA	NA
B3754X1GR1	3-PLY #375 1/4 X 1/16 GRADE 1	0.235	PIW	1/2"	20"	190, 1-1/2	550,R5-1/2, R6	NA	NA	NA
B4404X1	4-PLY #440 1/4 X 1/16	0.27	PIW	9/16"	20"	190, 1-1/2	550,R5-1/2,R6	NA	NA	NA
B4404X1HT	4-PLY #440 1/4 X 1/16 400 DEGREE	0.215	PIW	9/16"	24"	190, 1-1/2	550,R5-1/2,R6	NA	NA	NA
B4406X2	4-PLY #440 3/8 X 1/8	0.34	PIW	11/16"	20"	1-1/2, 2	550,R6,BR10	NA	NA	NA
B6006X2	3-PLY #600 3/8 X 1/8	0.335	PIW	11/16"	24"	1-1/2,2	550,R6,BR10	NA	NA	NA